

EASY 200

Digital Camera

Interpolate up to 6.6 Megapixels



6.6 INTERPOLATE UP TO
2.0 MEGAPIXEL
4X DIGITAL
ZOOM

- **4X** Digital Zoom Feature
- **1.5"** TFT LCD monitor to preview photos
- High Resolution **1600 X 1200** CMOS sensor with **2.0** Megapixels
- Store images with **16MB** of internal flash memory plus removable **SD** or **MMC** card
- Date and Time stamp your photos conveniently

LARGAN Digital

MASS STORAGE	IMAGE QUALITY	SENSOR
<p>PC MAC</p> <p>Data transfer</p>	<p>*840X480 *1024X768 *1600X1200 *2976X2240 *360,000 pixels *800,000 pixels *2 Megapixels *8 Megapixels *small/web use *small prints *large prints *poster-size prints</p> <p>Choose between 4 different image resolutions to suit your photo needs.</p>	<p>Powered by the super CMOS system for high quality photos.</p>
EXPOSURE COMPENSATION	6 SCENE MODES	LENS
<p>Before After</p> <p>* The settings can be adjusted in 1/2 intervals between the range of -2.5EV~+2.5EV.</p> <p>Adjust the exposure compensation setting to obtain the optimum image brightness (Exposure) when the subject is much brighter or darker than the background.</p>	<p>Just choose a mode like Portrait or Landscape, and the camera automatically handles all the adjustments for you.</p> <p>Includes : Portrait / Landscape / Back Light / Tungsten / Night Landscape / Fluorescent</p>	<p>The professional multi-coating lens ensures low distortion, high quality images every time.</p>

SPECIFICATIONS		SYSTEM REQUIREMENTS (PC)
Sensor Resolution	Protocol	1. Windows 98 / ME / 2000 / XP
1600 x 1200 CMOS sensor with 2.0M pixels	Mass Storage	2. A Pentium, Pentium II or higher PC, or compatible computer with MMX
Image Resolution	Self Timer	3. A hard disk with at least 200 MB space available to run the program
Still Mode:1600x1200;1024x768;640x480 pixels	10 seconds	4. At least 64 MB of RAM (128 MB recommended)
Video Clip:320 x 240 pixels	Image Type	5. Built-in USB port
Interpolation	JPEG	SYSTEM REQUIREMENTS (MAC)
2976 x 2240 pixels (6.6M pixels)	Image Capacity	1. OS 9.1 or above
Lens	16MB internal flash memory	ACCESSORIES
f=8.79mm	Removable SD or MMC card	1. USB cable
(4X Digital Zoom / fixed focus)	Continuous Shots / Strobe	2. Wrist strap
Focus Range	Yes	3. Li-ion rechargeable battery
48 inches (1.22m) to infinity	Power Source	4. Li-ion battery charger
Focus Range-Macro Mode	USB 5V / Li-ion rechargeable battery (3.7V)	5. User's manual
8 inches (0.2m)(macro mode)	Power Saving	6. TV cable
Shutter	Yes	7. CD
Electronic shutter	Dimensions	8. Leatherette camera case
LCD Display	3.54"(W) x 2.24"(H) x 0.7"(D)	
TFT LCD (1.6")	90 x 57 x 18 mm	
Interface	Video-Out	
Mini USB	Live/Still (Preview)	
	Weight	
	76g (without battery & SD card)	

LARGAN Inc.
2432 W. Peoria Avenue Building 9,
Suites 1165-1166 Phoenix, AZ 85029
Sales:1-877-4LARGAN (1-877-452-7426)
Tel:(602)944-6116
Fax:(602)944-6226
http://www.largan.com
e-mail:sales@largan.com

LARGAN Digital Co., Ltd
5F #6, 16th Road Taichung Industrial
District, 407, Taichung, TAIWAN
TEL: +886-4-36001100
FAX: +886-4-36012366

2.0
MEGAPIXEL
4X DIGITAL ZOOM

1-639-10-0001-04